SUPERTHERM SERIES

ALUMINIUM ENTRANCE DOORS





Why Choose Supertherm Series Doors?

Supertherm entrance doors are designed and manufactured predominantly for the German market. All doors are precision built using the latest technology and are fully equipped with reputable German hardware. All doors are made to suit your exact requirements, with complete freedom to customize the entrance to your home.

Rigid Make Up, all doors are flush inside and outside, 77mm deep, fully insulated, thermally broken and bonded with 3mm thick aluminium skins.

German Hardware, all doors are complete with GU automatic locking, BKS security cylinders and Dr Hanh hinges.

Advanced Glazing, all doors are complete with quadruple glazed laminated glass to the door wing and triple glazed laminated glass to the side lights.

U Values, exceptionally low U values of only 0.91 W/m2k on certain models. Which means a significant reduction in heat loss and savings on your energy bills.

Short Lead Times, all doors are available on lead of 4 to 6 weeks.

Door Configurations Available:







Ultra Modern Door Designs, with over seventy

Endless Colour Options, We offer a full range

standard Ral colours, a range of popular textured,

Hardware Choices, there are many different sizes and styles of both internal and external

handles, a choice of hinge and additional ancillary

Sophisticated Entry, there are optional

electronic finger print readers, digital key pads,

electric strike plates and remote access devices

Phenomenal Value for Money, we take pride in

offering market leading products at competitive

bespoke door designs to choose from.

metallic and even wood colours.

to suit your requirements.

available.

rates.







| Specification - Supertherm Series | | | | |
|-----------------------------------|----------------------------|--|--|--|
| Outer Frame Depth | 77mm | | | |
| Door Sash Depth | 77mm | | | |
| Maximum Door Size | 1200 x 2500 | | | |
| Maximum Side Lights | 1200 x 2500 | | | |
| Maximum Fan Light | 1200 x 1200 | | | |
| Glazing to Door Wing | Quadruple Glazed Laminated | | | |
| Glazing to Side Light/Top Light | Triple Glazed Laminated | | | |
| Aluminium Panel Thickness | 3mm Bonded | | | |
| Threshold Type | Low / Rebated Threshold | | | |
| Frame Extension | Available | | | |
| Door Sill | Available | | | |
| Stainless Trims | Flush | | | |
| U Value | 0.91 W/m2k (Achievable) | | | |
| Security | RC2 / RC3 (Achievable) | | | |
| | | | | |











Standard Door Features

Supertherm aluminium entrance doors are designed to offer high performance, an elegant appeal, flush contemporary sight lines and are manufactured to cater for the highest standards in Europe.

All doors are complete with German hardware, advanced glazing units, flush thermally broken, fully insulated profiles.

As standard all doors are complete with the following attributes:

- ▶ 77mm Deep Flush Both Sides
- 3mm Aluminium Skins Both sides
- Quadruple Glazed Laminated Units to Door Wing
- Triple Glazed Laminated Units to Side Lights/Top Lights
- Dr Hanh Roller Hinges 3 Number
- GU Automatic 5 Point Locking System
- **BKS Security Cylinder with 5 Keys**
- External Pull Handle Choice of Designs & Sizes
- Internal Lever Handle Choice of Designs
- Security Rosettes Both Sides
- 20mm Low Threshold
- Frame Extensions Available
- 150mm Extruded Doors Sills Available
- Any RAL Colour / A Choice of Textured Colours / Metallic Colours





Door Models

| | L101 | L110 | | L121 | L123 |
|------|------|------|------|------------|------|
| L130 | L140 | L150 | L160 | L161 | L162 |
| L170 | | L180 | L190 | 39 L200 | L210 |

L211

L124

L165

| L212 | | L224 | - - L230 | L231 | L240 |
|---|------|------|----------------|------|------|
| L241 | L251 | | L261 | L270 | L280 |
| 39 1 1 1 1 1 1 1 1 1 1 | L301 | L302 | | L310 | L311 |

| L312 | L313 | L320 | L330 | L331 | L335 | L337 |
|------|------|------------------------|------|------|------|------|
| L340 | L350 | - 44 - 44 - 1251 | L360 | - | L370 | L371 |
| | L380 | L381 | L383 | L385 | L390 | L391 |

6



















L430

SP01



SP02















SP06



SP03



SP04

Popular Standard RAL Colours Wooden Colours Any Standard RAL Colour RAL 7016 RAL 9005 RAL 7021 RAL 7012 RAL 9016 RAL 5003 RAL 3005 Golden Oak B2119 **Popular Textured Colours** Nussbaum B1523 RAL 7016 YL316F RAL 9005 YN305F RAL 7015 YL315F RAL 7021 YL321F RAL 7039 YL339F RAL 7040 YL340F RAL 5023 YJ323F RAL 1015 YD315F Popular Metallic Colours B1816 B1511 NOIR 2200 SABLE ORANGE 2100 MARS 2525 Vert 2500 Sable GONDAR 2525 Bronze 2525 Gris 2900 Sable Bleu 2700 Sable YW360F SABLE YW386I SABLES YX355F YW354F YW106I YW283F YW355F YW353F Interpon.

Glazing Styles Available





EVERY COLOR IS GREEN

External Pull Handles



Internal Lever Handles






E625


E701



E702

E703






Sight Lines


Single Door With Top Light


All doors with top lights will be supplied as separate frames.

77mm



Single Door





As standard all doors are complete


with a frame extension to provide

extension an extruded door sill can


XPS

ALUMINIUM


25mmX25mm



Single Door Outer Frame



Single Door With Side Light As One Frame



Single Door With Side Light As Separate Frames

Dependent on the overall size of the door and side light(s) required. The door and side light(s) will be supplied as separate frames.

